

4T-4 STROKE ENGINE OIL

DESCRIPTION

4T-4 STROKE ENGINE OIL is multi-grade (20W/50) superior lubricating oil developed specifically for large motorcycle four-stroke gasoline engines working under severe duty conditions.

APPLICATIONS

4T-4 STROKE ENGINE OIL is highly recommended for 4 Stroke motor engines such as Honda, Suzuki, Kawasaki, Yamaha and other motor cycles.

BENEFITS

- Having stable viscosity both at low and high temperatures.
- Prevent wet clutch slippage
- Excellent oxidations stability under exposure to high operating temperature
- Keeping engine clean and providing excellent protection against piston deposit formation
- Providing optimum protection against rust and keeping engine parts from wear.
- Keeping motor engine operate much better so that transmission friction is made as minimum as possible.
- Protect vital gear & clutch component to extend its service life.

PERFORMANCE LEVEL

API.....SL/CF
 ACEA.....A3/B3/04
 MB.....229.1
 VW.....505 00
 JASO.....MA

PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
Grade		-	20W/50	-
Specific Gravity	@ 15°C	-	0.8950	ASTM D-1298
Viscosity	@ 40°C	mm ² /s	150.5	ASTM D-445
	@ 100°C	mm ² /s	17.75	ASTM D-445
Viscosity Index		-	130	ASTM D-2270
Flash Point	COC	°C	240	ASTM D-92
Pour Point		°C	-27	ASTM D-97
Base Number		mg KOH/g	8	ASTM D-2896
Color		-	L3.5	ASTM D-1500
CCS Vis	@-15°C	cP	8500	ASTM D-5293