

ATF DEXRON III

DESCRIPTION

ATF DEXRON III is a high performance, multifunctional power transmission fluid satisfying both General Motors GM Dexron III, Ford revised friction modified Mercon and Allison C-4 specifications.

APPLICATIONS

ATF DEXRON III is recommended for passenger car and commercial vehicle with automatic transmission, hydraulic systems of mobile and off-high way equipment and industries equipment applications.

BENEFITS

- Friction modifier provides smooth shifting & trouble free operations.
- Excellent oxidation resistance resulting in cleaner transmissions.
- Compatible with all types of rubbers, elastomers and metals and provides protection against wear and leakage.
- Excellent low-temperature fluidity.
- Better shear stability.
- Better component compatibility.

PERFORMANCE LEVEL

Approved GM.....Dexron III H
 Revised Ford Mercon
 Allison.....C4
 Allison.....TES-389

PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
Grade		-	ATF D III-H	-
Specific Gravity	@ 15°C	-	0.8540	ASTM D-1298
Viscosity	@ 40°C	mm ² /s	34.30	ASTM D-445
	@ 100°C	mm ² /s	7.300	ASTM D-445
Viscosity Index		-	185	ASTM D-2270
Flash Point	COC	°C	185.0	ASTM D-92
Pour Point		°C	-42	ASTM D-97
Color		-	Red	VISUAL