

# AUTO COOL

## 33%, 40%, 50%, 100%

### DESCRIPTION

AUTO COOL, formulated from mono-ethylene glycol (MEG), is recommended for use in liquid cooling systems of automotive and industrial gasoline and diesel engines. They are available in various concentrations ready for use. It is harmless to rubber and does not foam or clog radiators.

### APPLICATIONS

AUTO COOL protects cooling systems of gasoline and diesel engine against rust in all seasons. It provides ideal cooling, effective protection against corrosion and scale deposit formation in the cooling systems year-round, resulting in longer radiator life.

### BENEFITS

- High boiling point gives better cooling performance in high temperature condition.
- Excellent anti-foam properties.
- Protects the radiator against rust & corrosion.
- Compatible with ordinary summer coolant.
- Protection against excessive evaporation.
- Provides year round cooling properties.

### PERFORMANCE LEVEL

BS.....6580  
ASTM..... D3306

Complies with most engine manufacturer's requirements for fulfill coolants.

### PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE				TEST METHOD
Grade		-	33%	40%	50%	100%	-
Specific Gravity	@ 20°C	-	1.050	1.052	1.055	1.130	ASTM D-1298
Color		-	Blue	Blue	Blue	Blue	ASTM D-1500
pH			8.0	7.9	7.9	-	ASTM D-1287